

NYLON CABLE TIE 200/250/300/400 X 4.8MM UV BLACK

FEATURES

Made from Polyamide6,6, Halogen Free Cable Tie
Head/pawl integrally moulded for added strength, bent tip design
Smooth round edges, safe and will not cut insulation
UV stabilised for outdoor use

PRODUCT DESCRIPTION

Strength, durability and adjustability are paramount in the design and development of our cable ties. Our nylon cable ties are made from halogen free PA66 nylon with an integrally moulded head and pawl. This, combined with intimate locking engagement between the pawl and strap teeth, means that our cable ties have high durability and strength without any metal parts. Our cable ties are designed to meet applicable strength requirements without sacrificing

ease of use. In fact, our cable tie design incorporates several measures to improve comfort and safety. The product has smooth, round edges that are more comfortable to work with and reduce the risk of cuts to cable insulation or hands. The tail of the tie features a bent-tip with v-shaped grooving that prevents your grip from slipping. This means less effort during pick-up, insertion and pull through.

Our UV stabilised black cable ties are suitable for outdoor applications.

TECHNICAL DATA

Loop Tensile Strength: 22kg
Bundle Diameter: 76mm
Length: 200/250/300/400mm
Width: 4.8mm
Thickness: 1.4mm
Colour: Black
Conformant Standards: UL
Refer: Mil-S-23190E-testing

Smoke Emission: Low smoke/halogen free
Material: PA66 with UV stabilisers
UV Stability: 2.5% carbon black for UV protection
Breakdown Voltage: 20kV/mm
Moisture Content: 2.5% w.v. @ 23%/50% RH
Operating Temperature: -40 to +85 degrees Celsius
Flammability: Passed U.L. 94V-2



Solar Rains Pty Ltd
ABN: 316 257 828 90
Phone: 0425 142 535
Info@solarrains.com.au